






# SWIVELS COMPARISON CHART

	 TAIMI	 A	 B	 C	 D
<b>Max Operating Pressure-Size 16 (PSI)</b>	6000	3000/5000	4000/5000	3000/5000	3000
<b>Wear Resistance</b>	Best	Good	Poor	Poor	Poor
<b>Side Load Resistance</b>	Best	Good	Poor	Poor	Poor
<b>Dismantling / Pulling Apart Resistance</b>	Best	Poor	Poor	Poor	Poor
<b>Possible Heavy Oil Spill Caused by Failure</b>	No	Yes	Yes	Yes	Yes
<b>Resistance to Leakage</b>	Best	Good	Poor	Poor	Poor
<b>Quick, Cheap and Easy Maintenance</b>	Yes	Average	No	No	No
<b>Possible Integration into Manifolds</b>	Yes	No	No	No	No
<b>Body Size</b>	Medium	Large	Compact	Compact	Compact
<b>Size of Tools Required to Service</b>	Small	Large	Medium	Medium	Medium
<b>Protections against Outside Contamination</b>	Best	Poor	Average	Average	Average
<b>Seal Protection against Pressure Peaks</b>	High	Poor	Poor	Poor	Poor
<b>Outside Lock Screw that Can Be Damaged</b>	No	Yes	Yes	Yes	Yes
<b>Spare Parts Availability</b>	Yes	No	No	No	No
<b>Durability</b>	Best	Good	Poor	Poor	Poor
<b>Available in 90 degrees</b>	Yes	Yes	Yes	Yes	Yes
<b>Available Sizes</b>	up to 32	up to 16	up to 32	Up to 32	Up to 32